

# TX-5353SW230C30F14-03H952770


## PRODUCT SPECIFICATION (R&D version)

### Features:

- Excellent transiting heat from LED chip operating under 6A.
- Provide uniform cross distribution of positive white and warm white dual color scheme, mixed pure.
- High luminous output.
- No UV.
- Encapsulated materials are environmentally certified and meet environmental requirements.

C<sup>0</sup>

Part No.	TX-5353SW230C30F14-03H952770	Spec No.	R&D version	Page	1 of 4
----------	------------------------------	----------	-------------	------	--------

**Package Dimensions:**

Part No.	TX-5353SW230C30F14-03H952770	Spec No.	R&D version	Page	2 of 4
----------	------------------------------	----------	-------------	------	--------

**TYANSHINE**



Pâ

## Electrical Optical Characteristics (Tc=25°C)

Parameter	Symbol	Condition	Emitting color	Min.	Typ.	Max.	Units
Luminous Flux	v	If=5.5A	S	—	15000	—	lm
			W	—	20000	—	
Forward Voltage	Vf	If=5.5A	S	39	42	45	V
			W	39	42	45	
Correlated Colour Temperature	CCT	If=5.5A	S	2600	2700	2740	K
			W	6600	7000	7200	
Viewing Angle at 50% IV	2 <sub>1/2</sub>	If=5.5A	S	—	115	—	Deg
			W	—	115	—	
Reverse Current	I <sub>R</sub>	—	—	—	—	—	μA
Color Rendering Index	Ra	If=5.5A	S	95	—	—	—
			W	95	—	—	

**Notes:**

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2.  $2_{1/2}$  is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
3. Luminous flux measurement tolerance:  $\pm 15\%$ .
4. Forward voltage measurement tolerance:  $\pm 3\%$ .
5. Ra measurement tolerance: 2.