

TX-5353SW330C36F17-03H952770


PRODUCT SPECIFICATION (R&D version)

Features:

- Excellent transiting heat from LED chip operating under 5A.
- Provide uniform cross distribution of positive white and warm white dual color scheme, mixed pure.
- High luminous output.
- No UV.
- Encapsulated materials are **HV** environmentally certified and meet environmental requirements.

Chip Material

Part No.	TX-5353SW330C36F17-03H952770	Spec No.	R&D version	Page	1 of 3
----------	------------------------------	----------	-------------	------	--------

Package Dimensions:

Part No.	TX-5353SW330C36F17-03H952770	Spec No.	R&D version	Page	2 of 3
----------	------------------------------	----------	-------------	------	--------

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

Electrical Optical Characteristics (Tc=25°C)

Parameter	Symbol	Condition	Emitting color	Min.	Typ.	Max.	Units
Luminous Flux	v	If=5A	S	—	15000	—	lm
			W	—	22000	—	
Forward Voltage	Vf	If=5A	S	47	49	51	V
			W	47	49	51	
Correlated Colour Temperature	CCT	If=5A	S	—	2700	—	K
			W	—	7000	—	
Viewing Angle at 50 IV	2 _{1/2}	If=5A	S	—	115	—	Deg
			W	—	115	—	
Reverse Current	I _R	—	—	—	—	—	μA
Thermal Resistance Junction to Case	R _{J-C}	If=5A	S	—	0.12	—	K/W
			W	—	0.12	—	
Color Rendering Index	Ra	If=5A	S	—	95	—	—
			W	—	95	—	

Notes:

- 1.Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3.Luminous flux measurement tolerance: $\pm 15\%$.
- 4.Forward voltage measurement tolerance: $\pm 3\%$.
- 5.Ra measurement tolerance: 2.